

# LED U Bend 6" Type A

SKU: AA-600052



## Description

The new LED Type A T8 is direct replacement for traditional fluorescent T8 tubes, providing instant, flicker-free illumination with lower energy costs. Type A Tubes are compatible with instant ballasts or programmed start ballasts.



## Features

- DLC 5.1, P, UL & CUL Classified
- AC100-277/347V Ballast Dependent
- High Lumen Efficiency
- CRI: >80
- Color Temperature: 5000K
- Lifetime: > 50,000 Hours
- Compatible With Instant & Programmed Start Ballast
- Works With IS+PS+RS+EM
- 10 Year Warranty, Extended Warranty Available

## Applications

Replaces Traditional Fluorescent T8s



Industrial Spaces



Commercial Lighting



Schools



Retail Stores

## Ordering Information



SKU	Model	DLC Product ID	CRI	Voltage	Wattage	Efficacy	Lumens	CCT	Socket	Finish	Size
AA-600033-SP	T8U-IDDM13-1800-L-CBA	P56Q4FK9	>80	AC100-277/347V	11.5W	128LM/W	1800LM	4000K	G13	White	48"
AA-600034	KK-T8-4EW-14-5AAD	PD182D6R	>80	AC100-277/347V	14.5W	134LM/W	1941LM	5000K	G13	White	48"
AA-600036-SP	T8U-IDDM13-2200-L-CBA	PAQMGMB7	>80	AC100-277/347V	15W	126LM/W	2200LM	5000K	G13	White	48"
AA-600037-SP	T8U-IDDM13-2200-L-EBA	P5SPFY74	>80	AC100-277/347V	15W	126LM/W	2200LM	5000K	G13	White	48"
AA-600040	T8L-IDDM13-1250-2ft-ECA-91	PQ6KQAU3	>80	AC100-277/347V	9W	120LM/W	1150LM	5000K	G13	White	24"
AA-600046	T8L-IDDM11-1600-4ft-EBA	PASFHRYF	>80	AC100-277/347V	12W	120LM/W	1800LM	5000K	G13	White	48"
AA-600052	T8U-IDDM11-2200-L-EBA	P5SPFY74	>80	AC100-277/347V	17W	126LM/W	2200LM	5000K	G13	White	6"
AA-600054-2B	T5L-IDDM14-3500-4FT-EBA-2B	P2X3LEJS	>80	AC100-277/347V	25W	120LM/W	3500LM	5000K	G13	White	48"