Elakeview Enterprise LTD



LED Canopy 40W AC120-277V 4000K

Product description:LED Canopy 40W AC120-277V 4000KModel Name:CP40WUNV40KOrder SKU:700034-4K



◊ Features


- Energy savings up to 70% vs 150W MH
- Sealed die-casting profile for both indoor and outdoor applications
- Three ½" threaded conduit and one ¾" conduit entry points
- High quality of heat-resisting polycarbonate optical lens
- Ultra thin, low profile design




◊ Specifications

| Rated Voltage (V) | 120-277V |
|----------------------------|----------------------|
| Rated Wattage (W) | 40W |
| Frequency (Hz) | 50/60 Hz |
| Rated Input Current (mA) | 0.37A Max |
| Power Factor | 0.9 |
| Luminous Flux (LM) | 5,092.6 LM |
| Color Temperature | Cool Light 4000K |
| Color Rendering Index (Ra) | 80 |
| Beam Angle | 155C |
| Lamp Efficacy (LM/W) | 130.11LM/W |
| Rated Lamp Lifetime (h) | 50,000 |
| Dimming | 1-10V Dimming |
| Dimension (mm) | 255.44*255.44*106.55 |
| IP Rating | 65 |
| Operating Temperature | -40 to 40 degC |
| Material | Aluminum + PC Lens |
| Certificate | UL, CUL, Rohs |

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM





Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance

